



**SAFETY DATA SHEET**  
**COLOUR MATCH AEROSOL PAINT**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME	COLOUR MATCH AEROSOL PAINT
PRODUCT NO.	CCL014, CGP015, YAB128, YAV110, YAF107, YNC018, YNC019, YAB148, YAF066, YAV124, YNC020, YAF078, YAB096, YAV074, YAF030, YAB121, YAB023, YNC021, YNC022, YAF176, YAB169, YAB021, YAF128, YAF135, YAF156, YAF088, YAB033, YAF167, YAV107, YNC011, YNC012, YAF147, YAF184, YAV084, YAB180, YAB150, YAV087, YAF127, YAB001, YAD039, YAD022, YAB167, YAB101, YAW038, YAF136, YAV076, YAB062, YNC001, YAR054, YAF085, YAF158, YAF011, YAD028, YTA001, YNC013, YAV101, YAF048, YAB119, YAV091, YAW025, YAB143, YAF108, YAF077, YAB097, YAB070, YNC014, YAF081, YAF073, YNC025, YAF182, YAR087, YAB193, YAV094, YAF132, YAF151, YAB164, YAV089, YAB186, YAV102, YAF144, YNC002, YAB174, YAO003, YAB165, YNC026, YAW046, YAB134, YAV058, YAB141, YNC027, YAV106, YAB138, YAB181, YNC028, YAW028, YAF089, YAF038, YAD020, YAD029, YAF170, YAF164, YAV072, YAF146, YMW003, YAB060, YAY021, YAV088, YAX018, YAD036, YAR097, YAD027, YMW001, YAW026, YAB177, CGW015, YAF120, YAF064, YAC002, YAL005, YNC029, YAB158, YAR077, YAD023, YAB157, YAB099, YAB100, YAF180, YTA005, YAV022, YAV054, YAB145, YAB007, YAF148, YAB055, YAB123, YAR090, YNC015, YAB191, YNC016, YAF086, YAF059, YAB127, YGB014, YSB014, YMB014, YGW014, YPA014, WPF012, YAF166, WPF014, WPF015, WPF017, WPF018, WPF020, WPF021, QMB014, QGB014, CSB015, CPA015, YAF074, CGB015, CCL015, CPA014, CMB014, CGB014, YAB131, CSB014, CGP014, CGW014, YAV105, YAF139, YAB166, YAV090, CMB015, YAF117, YAB149, YAB179, YAF177, YAB192, YAD009, YAV118, YAF169, YAF079, YAB162, YAF137, YAB173, YAD038, YNC003, YAF067, YAF163, YAF093, YAR030, YAF162, YAF058, YAB098, YAF140, YMW002, YAD018, YAF149, YAF150, YAB163, YAV075, YAV085, YAB168, YAF175, YAF095, YAR063, YAD033, YAB182, YAB091, YAV061, YNC004, YNC005, YAF159, YNC006, YAV120, YNC007, YAV121, YAF183, YAB196, YAF072, YAV116, YNC008, YNC009, YNC010, YAF155, YAF083, YAB095, YAB135, CRP015, YNC024, YAF119, YAB172, YAB137, YAD037, YAF160, YAF040, YAD015, YAF076, YAF172, YAF103, YAF179, YAV064, YAF115, YAF153, YAB140, YAV069, YAF154, YNC017, YAF068, YAB125, YAF082
INTERNAL ID	C
APPLICATION	Paint
SUPPLIER	TETROSYL LIMITED BEVIS GREEN WORKS WALMERSLEY BURY BL9 6RE 0161 764 5981 0161 797 5899 info@tetrosyl.com

**2 HAZARDS IDENTIFICATION**

Extremely flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes.

CLASSIFICATION Xi;R36. F+;R12. R66, R67.

HUMAN HEALTH

See section 11 for additional information on health hazards.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

**COLOUR MATCH AEROSOL PAINT**

Name	EC No.	CAS-No.	Content	Classification
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	1-5%	R10 Xi;R36
ACETONE	200-662-2	67-64-1	30-60%	F;R11 Xi;R36 R66 R67
BUTANE/PROPANE BLEND	270-704-2	68476-85-7	10-30%	F+;R12.
BUTYL ACETATE -norm	204-658-1	123-86-4	10-30%	R10 R66 R67
ISO-BUTANOL	201-148-0	78-83-1	1-5%	R10 Xi;R37/38,R41 R67
PETROLEUM DISTILLATES	265-185-4	64742-82-1	<1%	Xn;R65. N;R51/53. R10,R66.
XYLENE	215-535-7	1330-20-7	1-5%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES****GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention immediately!

**INHALATION**

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place.

**INGESTION**

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

**SKIN CONTACT**

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

**SPECIAL FIRE FIGHTING PROCEDURES**

Beware, risk of formation of toxic and corrosive gases.

**SPECIFIC HAZARDS**

In case of fire, toxic and corrosive gases may be formed.

**PROTECTIVE MEASURES IN FIRE**

Leave danger zone immediately.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

**ENVIRONMENTAL PRECAUTIONS**

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

**SPILL CLEAN UP METHODS**

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Absorb spillage with non-combustible, absorbent material. Ventilate well. Prevent discharge of larger quantity to drain.

**7 HANDLING AND STORAGE**

**COLOUR MATCH AEROSOL PAINT****USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

**STORAGE CLASS**

Flammable liquid storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE/PROPANE BLEND	WEL	1000 ppm	1750 mg/m3	1250 ppm	2180 mg/m3	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	
PETROLEUM DISTILLATES	WEL		600 mg/m3			
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

**ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

**RESPIRATORY EQUIPMENT**

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

**HAND PROTECTION**

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration.

**EYE PROTECTION**

Wear tight-fitting goggles or face shield.

**OTHER PROTECTION**

Provide eyewash station. **AVOID ALL SKIN AND RESPIRATORY CONTACT!**

**HYGIENE MEASURES**

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

**SKIN PROTECTION**

Protection suit must be worn.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

COLOUR

Misc. colours

**10 STABILITY AND REACTIVITY**

**COLOUR MATCH AEROSOL PAINT****STABILITY**

No particular stability concerns.

**11 TOXICOLOGICAL INFORMATION****HEALTH WARNINGS**

This chemical can be hazardous when inhaled and/or touched. This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

**ROUTE OF ENTRY**

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Dangerous for the environment if discharged into watercourses.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

**14 TRANSPORT INFORMATION****GENERAL**

Full protective clothing should be worn when handling this product.



UK ROAD CLASS	2.1		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	#
ADR CLASS NO.	2.1	ADR CLASS	Class 2: Gases
ADR PACK GROUP	#	ADR LABEL NO.	2.1
CEFIC TEC(R) NO.	20G5F	RID CLASS NO.	2.1
RID PACK GROUP	#	UN NO. SEA	1950
IMDG CLASS	2.1	IMDG PACK GR.	#
EMS	F-D, S-U	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1950
AIR CLASS	2.1	AIR PACK GR.	#

**15 REGULATORY INFORMATION****LABELLING**

Irritant



Extremely Flammable

**RISK PHRASES**

R12                      Extremely flammable.

**COLOUR MATCH AEROSOL PAINT**

R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S25	Avoid contact with eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.

## DETERGENT LABELLING

15 - < 30%	Aliphatic hydrocarbons
------------	------------------------

## EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**16 OTHER INFORMATION**

## REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

## ISSUED BY

HS&E Manager.

REVISION DATE 02/07/2008

REV. NO./REPL. SDS GENERATED 8

## RISK PHRASES IN FULL

R10	Flammable
R11	Highly flammable.
R12	Extremely flammable.
R20/21	Harmful by inhalation and in contact with skin.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

## COLOUR MATCH AEROSOL PAINT

### DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.