

**SAFETY DATA SHEET**  
**A1 TECHNOLUBE 5W30 SEMI**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME                    A1 TECHNOLUBE 5W30 SEMI  
PRODUCT NO.                    TLG005, TLG025, TLG205, TLG199, ASX001, ASX050  
INTERNAL ID                    A  
APPLICATION                    Engine oil  
SUPPLIER                        A1 MOTOR STORES LIMITED  
   3 PECKLETON BUSINESS PARK  
   PECKLETON COMMON  
   LEICESTERSHIRE  
   01455 822000  
   01455 824444

**2 HAZARDS IDENTIFICATION**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION                R52/53.

**HUMAN HEALTH**

See section 11 for additional information on health hazards.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
BRANCHED ALKYLPHENOL AND CALCIUM BRANCHED ALKYLPHENOL			<0.5	Rep 3;R62. Xi;R38. N;R50/53.
CALCIUM LONG CHAIN ALKARYL SULPHONATE	271-877-7		<1%	R43,R53.
POLYALKYL ARYLAMINE	270-128-1		<1%	N;R51/53.
POLYOLEFIN POLYAMINE SUCCINIMIDE			1-5%	R53.
ZINC ALKYLDITHIOPHOSPHATE	272-028-3		<1%	Xi;R41. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES****GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

**NOTES TO THE PHYSICIAN**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

**INHALATION**

Get medical attention if any discomfort continues.

**INGESTION**

Consult a physician for specific advice.

**SKIN CONTACT**

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

**A1 TECHNOLUBE 5W30 SEMI****SPECIAL FIRE FIGHTING PROCEDURES**

No specific fire fighting procedure given.

**PROTECTIVE MEASURES IN FIRE**

Leave danger zone immediately.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

**ENVIRONMENTAL PRECAUTIONS**

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

**SPILL CLEAN UP METHODS**

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb spillage with non-combustible, absorbent material.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Avoid spilling, skin and eye contact. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

**STORAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs. Store in tightly closed original container in a dry, cool and well-ventilated place.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION****PROTECTIVE EQUIPMENT****PROCESS CONDITIONS**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

**ENGINEERING MEASURES**

Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

**RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

Goggles/face shield are recommended.

**OTHER PROTECTION**

Wear appropriate clothing to prevent reasonably probable skin contact.

**HYGIENE MEASURES**

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Clear liquid		
COLOUR	Brown		
BOILING POINT (°C)	>250°C	RELATIVE DENSITY	0.86
FLASH POINT (°C)	220°C		

**10 STABILITY AND REACTIVITY**

**A1 TECHNOLUBE 5W30 SEMI****STABILITY**

No particular stability concerns.

**11 TOXICOLOGICAL INFORMATION****HEALTH WARNINGS**

This chemical can be hazardous when inhaled and/or touched.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****RISK PHRASES**

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SAFETY PHRASES**

S56 Dispose of this material and its container to hazardous or special waste collection point.  
P14 Contains CALCIUM LONG CHAIN ALKARYL SULPHONATE. May produce an allergic reaction.  
S2 Keep out of the reach of children  
S46 If swallowed, seek medical advice immediately and show this container or label.

**16 OTHER INFORMATION****REVISION COMMENTS**

NOTE: Lines within the margin indicate significant changes from the previous revision.

**ISSUED BY**

HS&E Manager.

**REVISION DATE**

10/08/2005

REV. NO./REPL. SDS GENERATED 8

**RISK PHRASES IN FULL**

R38 Irritating to skin.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R53 May cause long-term adverse effects in the aquatic environment.  
R62 Possible risk of impaired fertility.

## A1 TECHNOLUBE 5W30 SEMI

### DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.