

**SAFETY DATA SHEET**
ALUMINIUM PAINT**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME ALUMINIUM PAINT
PRODUCT NO. ALP250
INTERNAL ID C
APPLICATION Paint
SUPPLIER TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com

2 HAZARDS IDENTIFICATION

Flammable. Irritating to skin. Harmful by inhalation and in contact with skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R20/21. Xi;R38. R10, R52/53.

ENVIRONMENT

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

HUMAN HEALTH

See section 11 for additional information on health hazards.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ETHYLBENZENE	202-849-4	100-41-4	10-30%	F;R11 Xn;R20
PETROLEUM DISTILLATES	265-185-4	64742-82-1	5-10%	Xn;R65. N;R51/53. R10,R66.
XYLENE	215-535-7	1330-20-7	30-60%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES**GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure breathing can take place.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

ALUMINIUM PAINT**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures.

Absorb spillage with non-combustible, absorbent material. Ventilate well. Prevent discharge of larger quantity to drain.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m3(Sk)	125 ppm(Sk)	552 mg/m3(Sk)	
PETROLEUM DISTILLATES	WEL		600 mg/m3			
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT**PROCESS CONDITIONS**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

ALUMINIUM PAINT**HAND PROTECTION**

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration.

EYE PROTECTION

Wear tight-fitting goggles or face shield.

OTHER PROTECTION

Provide eyewash station. AVOID ALL SKIN AND RESPIRATORY CONTACT!

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

SKIN PROTECTION

Protection suit must be worn.

9 PHYSICAL AND CHEMICAL PROPERTIES

COLOUR	Silver		
RELATIVE DENSITY	0.96 - 1.0 20	VISCOSITY	85.90 s 20
FLASH POINT (°C)	25		

10 STABILITY AND REACTIVITY**STABILITY**

No particular stability concerns.

11 TOXICOLOGICAL INFORMATION**HEALTH WARNINGS**

This chemical can be hazardous when inhaled and/or touched. This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. Vapour from this chemical can be hazardous when inhaled.

ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

14 TRANSPORT INFORMATION**GENERAL**

Full protective clothing should be worn when handling this product.



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30

ALUMINIUM PAINT

ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-E	MFAG	See Guide
MARINE POLLUTANT	No.	UN NO. AIR	1263
AIR CLASS	3	AIR PACK GR.	III

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

XYLENE

RISK PHRASES

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S2	Keep out of the reach of children
S13	Keep away from food, drink and animal feeding stuffs.
S24	Avoid contact with skin.
S36/37	Wear suitable protective clothing and gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

DETERGENT LABELLING

5 - < 15% Aliphatic hydrocarbons

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

ISSUED BY

HS&E Manager.

REVISION DATE

19/09/2005

REV. NO./REPL. SDS GENERATED 5

ALUMINIUM PAINT

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.