



SAFETY DATA SHEET

STP DIESEL INJECTOR CLEANER (UK)

According to Regulation (EC) No 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	STP DIESEL INJECTOR CLEANER (UK)
APPLICATION	Fuel Additive
SUPPLIER	Clorox Europe Ltd, Unit 16, Rassau Industrial Estate, Ebbw Vale, Gwent NP23 5SD, UK Tel: 44 (0) 1495 350234 Fax: 44 (0) 1495 350234 EURegulatory@clorox.com
EMERGENCY TELEPHONE	+44 1495 350234 Monday - Thursday: 8.30 - 17.00 Friday: 8.30 - 15.30

2 HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. Harmful: may cause lung damage if swallowed. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xn;R65. R52/53, R66.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ODOURLESS KEROSENE	265-149-8	64742-47-8	60-100%	Xn;R65. R66.
POLYOLEFIN ALKYL PHENOL ALKYL AMINE			1-5%	Xi;R36/38.
SOLVENT NAPHTHA (PETROLEUM) LIGHT AROMATIC	265-199-0	64742-95-6	1-5%	Xn;R65. Xi;R37. N;R51/53. R10,R67.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.

INGESTION

Rinse mouth thoroughly. DO NOT induce vomiting if swallowed chemical is dissolved in petroleum-based material. Danger of aspiration and development of chemical pneumonia. Get medical attention immediately!

SKIN CONTACT

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing. Contaminated clothing should be laundered before use.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Water spray, fog or mist. Foam. Carbon dioxide (CO₂). Dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid water in straight hose stream; will scatter and spread fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Solvent vapours may form explosive mixtures with air.

STP DIESEL INJECTOR CLEANER (UK)

SPECIFIC HAZARDS

Fire creates: Oxides of: Nitrogen. Carbon.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Avoid discharge to the aquatic environment.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Avoid inhalation of vapours.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep upright. Ground container and transfer equipment to eliminate static electric sparks.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. Explosion-proof general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves made of: Neoprene. or Nitrile. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Use barrier creams to prevent skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Colourless to Straw
ODOUR	Hydrocarbon
SOLUBILITY	Insoluble in water
FLASH POINT (°C)	75°C PM Closed cup.

STP DIESEL INJECTOR CLEANER (UK)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

HAZARDOUS DECOMPOSITION PRODUCTS

Oxides of: Carbon. Nitrogen.

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapour may irritate respiratory system or lungs.

INGESTION

Harmful: may cause lung damage if swallowed. May cause discomfort if swallowed. Nausea, vomiting. Diarrhoea. Central nervous system depression.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking. Prolonged contact will result in defatting of the skin leading to irritation and possibly dermatitis.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Avoid discharge to the aquatic environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Triple rinse drums prior to recycling or disposal.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS

ODOURLESS KEROSENE

RISK PHRASES

R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.

SAFETY PHRASES

S2	Keep out of the reach of children
S23B	Do not breathe vapour.
S24/25	Avoid contact with skin and eyes.

STP DIESEL INJECTOR CLEANER (UK)

S35	This material and its container must be disposed of in a safe way.
S62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

NATIONAL REGULATIONS

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

16 OTHER INFORMATION

REVISION COMMENTS

Re-issued in accordance with Regulation (EC) No. 1907/2006 Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). Supplier name amended.

REVISION DATE 05-2008

REV. NO./REPL. SDS GENERATED 2 / 11-2005

RISK PHRASES IN FULL

R10	Flammable.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

The information supplied here is accurate to the best knowledge and belief of Clorox Car Care, it is however, not intended as a warranty or representation, and should not be construed as such, for which Clorox Car Care assumes any legal responsibility. Any information or advice obtained from Clorox Car Care other than by means of this publication, and whether relating to Clorox Car Care's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Clorox Car Care when used instead of, or in conjunction with materials supplied by Clorox Car Care, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Clorox Car Care accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.